

KVVR-铜芯聚氯乙烯绝缘聚氯乙烯护套控制软电缆

导体+绝缘+填充+护套

电缆规格		导体结构	绝缘厚度 mm		护套标称厚度 mm		成品参考外径 mm		成品参考重量kg/km	
芯数 n	截面 mm ²	根数/直径	450/750kv	0.6/1kv	450/750kv	0.6/1kv	450/750kv	0.6/1kv	450/750kv	0.6/1kv
2	0.5	16/0.20	0.6	0.8	1.2	1.8	7.2	9.2	55	88
	0.75	24/0.20	0.6	0.8	1.2	1.8	7.7	9.7	64	99
	1	32/0.20	0.6	0.8	1.2	1.8	8	10	72	108
	1.5	30/0.25	0.7	0.8	1.2	1.8	9	10.6	92	125
	2.5	50/0.25	0.8	0.8	1.2	1.8	10.3	11.5	126	156
3	0.5	16/0.20	0.6	0.8	1.2	1.8	7.6	9.6	65	101
	0.75	24/0.20	0.6	0.8	1.2	1.8	8	10.1	76	115
	1	32/0.20	0.6	0.8	1.2	1.8	8.4	10.5	87	128
	1.5	30/0.25	0.7	0.8	1.2	1.8	9.4	11	114	149
	2.5	50/0.25	0.8	0.8	1.2	1.8	10.8	12	160	191
4	0.5	16/0.20	0.6	0.8	1.2	1.8	8.1	10.3	77	118
	0.75	24/0.20	0.6	0.8	1.2	1.8	8.6	10.8	92	135
	1	32/0.20	0.6	0.8	1.2	1.8	9.1	11.2	106	151
	1.5	30/0.25	0.7	0.8	1.2	1.8	10.2	11.9	139	179
	2.5	50/0.25	0.8	0.8	1.2	1.8	11.8	13	199	233
5	0.5	16/0.20	0.6	0.8	1.2	1.8	8.7	11	90	136
	0.75	24/0.20	0.6	0.8	1.2	1.8	9.3	11.6	108	157
	1	32/0.20	0.6	0.8	1.2	1.8	9.8	12.1	125	176
	1.5	30/0.25	0.7	0.8	1.2	1.8	11	12.8	166	210
	2.5	50/0.25	0.8	0.8	1.2	1.8	13.4	14	258	276
6	0.5	16/0.20	0.6	0.8	1.2	1.8	9.4	11.8	100	151
	0.75	24/0.20	0.6	0.8	1.2	1.8	10	12.4	121	175
	1	32/0.20	0.6	0.8	1.2	1.8	10.5	12.9	141	197
	1.5	30/0.25	0.7	0.8	1.2	1.8	11.9	13.7	189	237
	2.5	50/0.25	0.8	0.8	1.5	1.8	14.5	15.1	293	313
7	0.5	16/0.20	0.6	0.8	1.2	1.8	9.4	11.8	107	159
	0.75	24/0.20	0.6	0.8	1.2	1.8	10	12.4	130	185
	1	32/0.20	0.6	0.8	1.2	1.8	10.5	12.9	153	210
	1.5	30/0.25	0.7	0.8	1.2	1.8	11.9	13.7	205	254
	2.5	50/0.25	0.8	0.8	1.5	1.8	14.5	15.1	319	340

8	0.5	16/0.20	0.6	0.8	1.2	1.8	10	12.5	121	179
	0.75	24/0.20	0.6	0.8	1.2	1.8	10.7	13.2	148	209
	1	32/0.20	0.6	0.8	1.2	1.8	11.3	13.8	174	238
	1.5	30/0.25	0.7	0.8	1.5	1.8	13.4	14.7	253	289
	2.5	50/0.25	0.8	0.8	1.5	1.8	15.6	16.2	366	387
10	0.5	16/0.20	0.6	0.8	1.2	1.8	11.5	14.3	148	217
	0.75	24/0.20	0.6	0.8	1.2	1.8	12.3	15.1	182	255
	1	32/0.20	0.6	0.8	1.5	1.8	13.6	15.8	232	291
	1.5	30/0.25	0.7	0.8	1.5	1.8	15.5	16.9	311	354
	2.5	50/0.25	0.8	0.8	1.5	1.8	18.2	18.8	453	478
12	0.5	16/0.20	0.6	0.8	1.2	1.8	11.8	14.7	167	241
	0.75	24/0.20	0.6	0.8	1.5	1.8	13.3	15.5	224	285
	1	32/0.20	0.6	0.8	1.5	1.8	14	16.3	263	327
	1.5	30/0.25	0.7	0.8	1.5	1.8	16	17.4	354	401
	2.5	50/0.25	0.8	0.8	1.5	1.8	18.7	19.3	520	545
14	0.5	16/0.20	0.6	0.8	1.2	1.8	12.4	15.3	188	268
	0.75	24/0.20	0.6	0.8	1.5	1.8	13.9	16.3	252	319
	1	32/0.20	0.6	0.8	1.5	1.8	14.7	17	296	367
	1.5	30/0.25	0.7	0.8	1.5	1.8	16.8	18.2	402	452
	2.5	50/0.25	0.8	0.8	1.5	1.8	19.7	20.3	592	619
16	0.5	16/0.20	0.6	0.8	1.5	1.8	13.6	16	227	297
	0.75	24/0.20	0.6	0.8	1.5	1.8	14.6	17	280	354
	1	32/0.20	0.6	0.8	1.5	1.8	15.4	17.9	331	409
	1.5	30/0.25	0.7	0.8	1.5	1.8	17.6	19.1	450	505
	2.5	50/0.25	0.8	0.8	1.7	1.8	21.1	21.3	686	695
19	0.5	16/0.20	0.6	0.8	1.5	1.8	14.2	16.8	254	330
	0.75	24/0.20	0.6	0.8	1.5	1.8	15.3	17.9	315	396
	1	32/0.20	0.6	0.8	1.5	1.8	16.2	18.8	374	459
	1.5	30/0.25	0.7	0.8	1.5	1.8	18.5	20.1	511	571
	2.5	50/0.25	0.8	0.8	1.7	1.8	22.2	22.4	781	791
24	0.5	16/0.20	0.6	0.8	1.5	1.8	16.3	19.3	312	405
	0.75	24/0.20	0.6	0.8	1.5	1.8	17.6	20.6	389	488
	1	32/0.20	0.6	0.8	1.5	1.8	18.7	21.7	462	567
	1.5	30/0.25	0.7	0.8	1.7	1.8	21.9	23.3	654	708
	2.5	50/0.25	0.8	0.8	1.7	1.8	25.8	26	973	985

27	0.5	16/0.20	0.6	0.8	1.5	1.8	16.6	19.7	340	441
	0.75	24/0.20	0.6	0.8	1.5	1.8	17.9	21	426	533
	1	32/0.20	0.6	0.8	1.5	1.8	19	22.1	508	621
	1.5	30/0.25	0.7	0.8	1.7	1.8	22.3	23.8	720	778
	2.5	50/0.25	0.8	0.8	1.7	1.8	26.4	26.6	1075	1087
30	0.5	16/0.20	0.6	0.8	1.5	1.8	17.2	20.4	370	478
	0.75	24/0.20	0.6	0.8	1.5	1.8	18.5	21.7	465	580
	1	32/0.20	0.6	0.8	1.7	1.8	20.1	22.9	573	677
	1.5	30/0.25	0.7	0.8	1.7	1.8	23.1	24.6	787	850
	2.5	50/0.25	0.8	0.8	1.7	1.8	27.3	27.5	1180	1192
37	0.5	16/0.20	0.6	0.8	1.5	1.8	18.4	21.8	439	566
	0.75	24/0.20	0.6	0.8	1.7	1.8	20.3	23.3	573	690
	1	32/0.20	0.6	0.8	1.7	1.8	21.6	24.6	684	808
	1.5	30/0.25	0.7	0.8	1.7	1.8	24.9	26.5	945	1020
	2.5	50/0.25	0.8	0.8	1.7	1.9	29.5	29.9	1425	1451
44	0.5	16/0.20	0.6	0.8	1.7	1.8	21	24.4	534	662
	0.75	24/0.20	0.6	0.8	1.7	1.8	22.6	26	672	809
	1	32/0.20	0.6	0.8	1.7	1.8	24.1	27.5	804	950
	1.5	30/0.25	0.7	0.8	1.7	1.9	27.8	29.8	1113	1214
	2.5	50/0.25	0.8	0.8	2	2	33.7	33.7	1726	1726
48	0.5	16/0.20	0.6	0.8	1.7	1.8	21.3	24.7	571	708
	0.75	24/0.20	0.6	0.8	1.7	1.8	23	26.5	720	868
	1	32/0.20	0.6	0.8	1.7	1.8	24.5	27.9	864	1020
	1.5	30/0.25	0.7	0.8	1.7	2	28.3	30.5	1199	1320
	2.5	50/0.25	0.8	0.8	2	2.1	34.3	34.5	1862	1877
52	0.5	16/0.20	0.6	0.8	1.7	1.8	21.8	25.4	610	757
	0.75	24/0.20	0.6	0.8	1.7	1.8	23.6	27.2	771	929
	1	32/0.20	0.6	0.8	1.7	1.9	25.1	28.9	926	1106
	1.5	30/0.25	0.7	0.8	1.7	2	29.1	31.4	1287	1415
	2.5	50/0.25	0.8	0.8	2	2.1	35.2	35.4	2001	2017
61	0.5	16/0.20	0.6	0.8	1.7	1.8	23.1	26.9	697	866
	0.75	24/0.20	0.6	0.8	1.7	1.9	25	29	885	1079
	1	32/0.20	0.6	0.8	1.7	1.9	26.6	30.6	1066	1271
	1.5	30/0.25	0.7	0.8	2	2	31.4	33.2	1528	1630
	2.5	50/0.25	0.8	0.8	2.2	2.1	37.8	37.8	2347	2347

