

	DSX-5000	DTX-1500	DTX-1800
Maximum Category/Class	6A / F <sub>A</sub>	6A / E <sub>A</sub>	6A / F
Accuracy Level	Level V draft	Level IIIe	Level IV
Maximum Frequency	1000 MHz	500 MHz	900 MHz
Autotest Time	10 sec Class E <sub>A</sub> /Cat 6A 9 sec Class E/Cat 6	22 sec Class E <sub>A</sub> /Cat 6A 9 sec Class E/Cat 6	22 sec Class E <sub>A</sub> /Cat 6A 9 sec Class E/Cat 6
Internal Memory	≈ 12,000 Cat 6A with plots	≈ 250 Cat 6A with plots ≈ 1500 Cat 6A without plots	≈ 250 Cat 6A with plots ≈ 1500 Cat 6A without plots
Battery Life	≈ 10 Hours	≈ 10 Hours	≈ 10 Hours
Cable Identifier Length	60 characters	25 characters	25 characters
Permanent Link Adapter	✓	Optional	✓
ProjX™ Project Management	✓		
Taptive™ Gesture-based User Interface	✓		
LinkWare™ Professional Reports	✓	✓	✓
LinkWare™ Live capable	✓		
Fault Info Troubleshooting	Advanced	Limited	Limited
PoE Resistance Unbalance	✓		
Integrated Alien Crosstalk Capability	✓		
TCL Measurement	✓		
Shield Integrity Test	✓		
Coax Adapters	Optional	Optional	Optional
M12 Adapters	Optional	Optional	Optional
Patch Cord Adapters	Optional		Optional
Fiber OLTS Module	Optional		Optional
Fiber OTDR Module	Optional		Optional
Automated Fiber Inspection	Optional		

	DSX-5000	DTX-1500	DTX-1800
纜線等級	6A / F <sub>A</sub>	6A / E <sub>A</sub>	6A / F
測試精度	Level V draft	Level IIIe	Level IV
最大頻率	1000 MHz	500 MHz	900 MHz
測試時間	Class E <sub>A</sub> /Cat 6A – 10秒 Class E/Cat 6 – 9 秒	Class E <sub>A</sub> /Cat 6A – 22秒 Class E/Cat 6 – 9 秒	Class E <sub>A</sub> /Cat 6A – 22秒 Class E/Cat 6 – 9 秒
內建記憶體	≈ 12,000 Cat 6A 有圖	≈ 250 Cat 6A 有圖 ≈ 1500 Cat 6A 無圖	≈ 250 Cat 6A 有圖 ≈ 1500 Cat 6A 無圖
電量	≈ 10 小時	≈ 10 小時	≈ 10 小時
纜線 ID 長度	60 字元	25 字元	25 字元
Permanent Link 模組	✓	選配	✓
ProjX™ 專案管理	✓		
Taptive™ 觸控介面	✓		
LinkWare™ 專業報告	✓		✓
LinkWare™ Live	✓		
Fault Info 功能	進階	一般	一般
PoE Resistance Unbalance	✓		
內建 Alien Crosstalk 模組	✓		
TCL 測試	✓		
完整遮蔽測試	✓		
Coax 模組	選配	選配	選配
M12 模組	選配	選配	選配
Patch Cord 模組	選配		選配
Fiber OLTS 模組	選配		選配
Fiber OTDR 模組	選配		選配
光纖端面檢視鏡	選配		