

General properties

- Nominal frequency 50 – 60 Hz
- Insulation class E
- Thermal rated short-term current $I_{th} = 60 \times I_N/1s$
- Thermal continuous current $1.2 \times I_N$
- Rated surge current $I_{dyn} = 2.5 \times I_{th}$, however min. 100 kA with all plug-in current transformers
- Highest voltage for operating equipment $U_m = 0.72$ kV
- Rated insulation level (test voltage) 3 kV / 1 min (per IEC 61869-2)
- Over-current limit factor FS5 with max. power or FS10 with min. power
- Harmonics current up to 50th harmonic
- Test report available
- Temperature range -25 to 55°C
- Other current transformer requirements on request



Technical data

Device overview calibratable moulded case current transformer, class 0,2S / 5 A secondary current									
Type	Primary current in A	Class	Power in VA	Transformation ratio	Primary conductor	Round conductor in mm	Width in mm	Weight (kg)	Item no.
ERM60-E3A	150	0.2S	1 VA	150/5 A	30 x 10	24,5	60	0,4	09.06.212
ERM60-E3A	200	0.2S	2 VA	200/5 A	30 x 10	24,5	60	0,4	09.06.213
ERM60-E3A	250	0.2S	2,5 VA	250/5 A	30 x 10	24,5	60	0,4	09.06.214
ERM70-E4A	300	0.2S	2,5 VA	300/5 A	40 x 10	30,5	70	0,4	09.06.215
ERM70-E4A	400	0.2S	5 VA	400/5 A	40 x 10	30,5	70	0,4	09.06.216
ERM70-E4A	500	0.2S	5 VA	500/5 A	40 x 10	30,5	70	0,4	09.06.217
ERM70-E4B	600	0.2S	5 VA	600/5 A	40 x 10	30,5	70	0,5	09.06.218
ERM70-E4B	750	0.2S	5 VA	750/5 A	40 x 10	30,5	70	0,5	09.06.219
ERM85-E6A	1000	0.2S	5 VA	1000/5 A	60 x 10	30,6	85	0,6	09.06.220

Accessories

Mounting clips ERM60/ERM70

09.09.012

These transformers are not on stock and will be ordered to customer order, products are excluded from return.

Basic Information for the use of current transformer can be found in chapter 10.