



Technical data

Communication Gateway for wireless and hard-wired communication	
Item number	15.06.088
Supply voltage	85 – 264 V AC (integrated power supply)
Frequency	44 – 440 Hz
Interfaces	
Ethernet 10 / 100 Base-TX	RJ45 (for hard-wired communication)
Communication	
UMTS / HSPA6+	yes (for fast internet connection via mobile network)
Integrated security module for secure, certificate-protected communication	yes
General data	
Operating system	Embedded LINUX
Processor	ARM 9
Cycle rate	400 MHz
Memory (RAM)	256 MB
Memory (Flash)	256 MB
Hardware	Watchdog and temperature monitoring
Screw-on antenna or external antenna via SMA antenna connector	yes
SIM card slot	integrated
Power supply	standard AC
Mechanical data	
Installation	35-mm DIN top-hat rail
Integrated wall fastening	yes
Housing	closed 3-part plastic housing
Protection class	IP20
LED indications	4 units (2-colour for commissioning and operating display)
Weight	280 g
Dimensions in mm (H x W x D)	63 x 106 x 90
Accessories	
AMR rubber antenna, 2 m cable	15.06.089
Extension cable, 5 m	15.06.091
Extension cable, 10 m	15.06.092
Angled antenna	15.06.093
INOX antenna mounting bracket	15.06.094