

Compact Weather Sensor for Wind with Compass



Measures Wind Speed and Direction

Includes a compass

Overview

The MetSENS200 compact weather sensor measures wind speed and direction via an ultrasonic sensor. An integrated electronic compass provides apparent wind measurements. WMO average wind speed and direction and gust data are provided.

The MetSENS200 is compatible and easily integrated with the MeteoPV Solar Resource Platform and any Campbell Scientific data logger using SDI-12, RS-485, ModbusRS-485, or NMEA RS-232.

Benefits and Features

- **)** Quality measurements
- **)** Fast and simple to install
- > Compact, integrated design

- Lightweight and robust
- > Two-year warranty

Specifications

Sampling Rate	1 Hz
Digital Communication Modes	Serial RS-232, RS-422, RS-485, SDI-12, NMEA, Modbus, ASCII
IP Rating	66
Compliance	CE, RoHS
Operating Temperature Range	-40° to +70°C
Operating Voltage	5 to 30 Vdc
Typical Current Drain @ 12 Vdc	25 mA (continuous high mode)0.7 mA (eco-power mode; 1 hour polled)

Weight 0.5 kg (1.1 lb)

Wind Speed Meas	urement
Measurement Range	0.01 to 60 m s ⁻¹
Accuracy	±3% (up to 40 m s ⁻¹) ±5% (up to 60 m s ⁻¹)
Resolution	0.01 m s ⁻¹
Starting Threshold	0.01 m s ⁻¹
Min of Divo etians M.	

Wind Direction Measurement

Measurement Range 0° to 359°





