Senseair Sunrise HVAC



Standard specification

Article No. Measured gas Operating principle Measurement range (CO₂)

Accuracy (CO₂)

Average current, typical Measurement period

Steady state current during sampling Peak current Power supply Dimensions Weight Life expectancy

Operating range Storage temperature

Serial communication

006-0-0008

Carbon dioxide (CO₂) Non-dispersive infrared 400 - 5000ppm; extended range up to 10000ppm ±30ppm ±3% of reading 1,2 (extended range ±10% of reading) See table to the right

Default: 16s, 8 samples (adjustable by host)

90mA <125mA 3.05 - 5.5V 3 33.5 x 19.7 x 11.5mm

>15 years

0-50°C, 0-85%RH

-40 - 70°C UART, I2C

Note 1: 15 - 35°C, 0 - 80%RH, after 3 ABC periods and default measurements

Document: PSH12460

Note 2: Specification is referenced to uncertainty of calibration gas mixtures ($\pm 1\%$). Note 3: Unprotected against surges and reverse power supply polarity.

A new generation NDIR sensor

Senseair Sunrise HVAC is a new generation NDIR sensor with Optical Solid State design. Electronics with no moving parts makes this sensor robust and resistant to vibrations. Any application with a tough environment or in environments with explosion risk is benefited by the solid state design.

It is the first NDIR sensor with LED technology that truly saves power while maintaining a high precision.

The ultra low power consumption makes Sunrise optimal for battery and wireless applications.

The sensor has an accuracy (CO₂) ±30 ppm ±3% of reading. Thanks to the built-in self-correcting algorithm you can mount and forget your sensor for the next 15 years and it will still be accurate.

Key benefits

- Optical Solid State
- Ultra Low Power consumption
- High Precision
- Robust
- Mass Production
- Self-correcting

Average current (typical), at continuous and single measurement mode respectively

Measurement period	2 Sam Cont	nples Single	8 Samples Cont Single		32 Samples Cont Single	
16s	22µA	g	34μΑ	59.5		9
1min 5min	18μΑ 16μΑ	7μΑ 1μΑ	21μΑ 17μΑ	17μΑ 3μΑ	35μΑ 20μΑ	27μΑ 5μΑ





